



AR3638 3/8" Super Duty Impact Wrench

- Single hammer impact mechanism for removing and replacing bolts easily
- More torque, less vibration
- Pistol-grip style, compact and lightweight
- Built-in positive action regulator, handle exhaust

Specifications:

| | |
|---------------------------------|--------|
| Bolt Capacity..... | 7/16" |
| Free Speed (RPM)..... | 10,000 |
| Max. Torque (Ft/Lb)..... | 180 |
| Avg. Air Consumption (CFM)..... | 2.5 |
| Air Pressure (PSI)..... | 90 |
| Air Inlet (NPT)..... | 1/4" |
| Hose Size (ID)..... | 3/8" |

Repair Kit: A3638K1

Packing: Blow Case



AR3641 1/2" Dr. Standard Impact Wrench

- Ideal tool for general purpose tire and transmission assembly work
- Built-in air regulator for complete speed control
- Vinyl boot protects tool against damage
- Single-handed forward and reverse power control

| | |
|---------------------------------|-------|
| Specifications:..... | 5/8" |
| Free Speed (RPM)..... | 7,000 |
| Max. Torque (Ft-Lb)..... | 230 |
| Avg. Air Consumption (CFM)..... | 4.5 |
| Air Pressure (PSI)..... | 90 |
| Air Inlet (NPT)..... | 1/4" |
| Hose Size (ID)..... | 3/8" |

Repair Kit: A3641K1

Packing: Blow Case



AR3651 1/2" Dr. Super Duty Impact Wrench

- Twin Hammer mechanism design for high torque performance
- Super duty wrench rated for industrial use
- Ideal for automotive, truck, and farm applications
- Quality construction, rugged dependability and long life

| | |
|---------------------------------|-------|
| Specifications:..... | 5/8" |
| Max. Torque (Ft/Lb)..... | 400 |
| Free Speed (RPM)..... | 7,000 |
| Avg. Air Consumption (CFM)..... | 4 |
| Air Pressure (PSI)..... | 90 |
| Air Inlet (NPT)..... | 1/4" |
| Hose Size (ID)..... | 3/8" |

Repair Kit: A3651K1

Packing: Blow Case