Engine



T70085

Steel



friction brake

- Heavy-duty construction
- · Positive locking ratchet

T70085

T70086 53-125mm, Height: 3" **T70087** 53-175mm, Height: 3" T70088 54-127mm, Height: 3-1/2" T70089 89-178mm, Height: 3-1/2" T70090 60-175mm, Height: 4" T70091 60-175mm, Height: 6" T70092 90-175mm, Height: 6" 40-80mm, Height: 2"

T75524

- · Wrinkle band design greatly reduces ring friction
- · Features thumbscrew precision adjustment
- Operates on most domestic and import vehicles

- Smooth gripping edge prevents damage to piston ring during installation
- · Capacity: 50 100mm



T70186 80 - 100mm

T75523





place while it removes carbon from piston grooves on 2-3/4" to 5"

- · Cutters rotate to the correct size and lock in place
- · Includes: three cutter wheels with sizes:

T70187 110 - 160mm

1.2, 1.5, 1.8, 2.0, 2.5, 2.8, 3, 4, 4.5, 5, 5.5mm 1/6", 5/64", 3/32", 1/8", 5/32", 3/16", 1/4"

T75860 Remove



imperfections

and ridges out of cylinder wall with a lathe-type action with one setting. There is no need to re-adjust the tool when changing from one cylinder to another. Removable tungsten carbide cutter and fine threaded feed screw ensure clean cut action. Operating range: 3" - 5" diameter cylinders