


Bearing Separators T75908



T75909 -50 - 75mm

T75910 -75 - 100mm

Available in 3 sizes

Model # T75908

- Capacity : 30mm - 50mm
- Bolt diameter : 3/8" x 24T x L120mm
- Extension rod : 3/8" x 16T

Model # T75909

- Capacity : 50mm - 75mm
- Bolt diameter : 1/2" x 20T x L135mm
- Extension rod : 3/8" x 16P

Model # T75910

- Capacity : 75mm - 105mm
- Bolt diameter : 5/8" x 18T x L165mm
- Extension rod : M12 x 1.75P

This device extracts bearings, double bearings, bearing cones and generator gears. Its curved, sharp edge maximizes the gripping surface area and locks the bearing in position. When space is limited, it can easily remove certain parts where the standard puller jaws cannot reach.

T75907 Bearing Separator Assembly Kit Includes



- Available in 3 sizes
- Bearing Separator
- Chrome Molybdenum steel
- Capacity: 30mm - 50mm
- Bolt diameter: 3/8" x L120mm x 24T
- Bearing Separator
- Chrome Molybdenum steel
- Capacity: 50mm - 75mm
- Bolt diameter: 1/2" x L135mm x 20T
- All necessary accessories

This kit easily extracts bearings, double bearings, bearing cones and generator gears even in confined areas where standard puller jaws cannot reach. The bearing separator's curved, sharpened edge maximizes the gripping surface area and locks the bearing in position. The push-puller secures its rods to the tapped holes of the bearing separator and pushes the object out. Screw power enables a smooth, effective pulling force that completes the task, damage-free.