



T80841
2000W Miter Saw

- Transparent moveable guard allows excellent visibility and operator safety
- Common angle stops
- Spindle lock for fast and easy blade replacement
- Large comfort switch and rubber D handle for enhanced control and comfort
- Dust collecting bag ensures clean working environment
- Soft Painting Finishing



Voltage/Frequency	230V~50Hz
Power	2000W
Speed	4500rpm
Blade Size	250mm
Miter/Bevel	
0° - 90°:	300×75mm
45° - 90°:	210×75mm
0° - 45°:	300×40mm
45° - 45°:	210×40mm



T80842
1900W Miter Saw



Voltage/Frequency	230V~50Hz
Power	1900W
Speed	4500rpm
Blade Size	255mm
Cutting Capacity	
0° - 90°:	134×72mm, 160×46mm
45° - 90°:	93×72mm, 112×41mm
0° - 45°:	150×41mm
45° - 45°:	100×41mm



T80921
1600W 254mm Compound & Slide Compound Mitre Saw

Motors Available	110V / 60Hz
No-Load Speed	3500 rpm (60Hz)
Power (W)	1600
Bevels	0 to 45 Degrees
Miters	0 to 45 Degrees Left and Right
Blade	254mm (10 in.)
Arbor	30mm (1-3/16 in.) or 25.4mm (1 in.)
Base Dimensions	460×450mm

Slide (GP-255S)	Cutting Capacities	90 Degree Miter: 300mm×60mm (11-13/16×2-3/8 in.)
		45 Degree Miter: 212mm×60mm (8-3/8×2-3/8 in.)
	Weight kg(lbs)	19.5 (42.9)
Non-Slide (GP-255)	Cutting Capacities	90 Degree Miter: 100mm×60mm (4×2-3/8 in.)
		45 Degree Miter: 76mm×60mm (3×2-3/8 in.)
	Weight kg(lbs)	18.5 (40.7)

Standard Accessories:

- * Arbor lock bar
- * M13 combination wrench
- * M10 combination wrench
- * M24/27 open-end wrench
- * Vacuum port
- * Vise (GP255S only)